

# Pan, tilt, and zoom capabilities for wide area coverage

Axis PTZ dome network cameras provide pan, tilt, and zoom functions, enabling wide area coverage and great details when zooming in. A wide range of accessories is available, including joysticks for easy maneuvering and mounting kits for indoor and outdoor installations.

## **AXIS Q60 PTZ Dome Network Camera Series**

Advanced, high-speed PTZ domes with mission-critical functions

AXIS Q60 PTZ Dome Network Cameras are designed for the most demanding video surveillance applications, with outstanding, full frame rate video in resolutions up to HDTV 1080p. With powerful zoom and high-speed, precision pan/tilt/zoom capabilities, the indoor and outdoor-ready PTZ domes enable exceptional coverage of large areas and great detail when zooming in. With guick and reliable installation features, the cameras are ideal for airports, seaports, stadiums, manufacturing plants as well as city and perimeter surveillance. Pressurized, stainless steel versions are ideal outdoors for marine, mining, and oil and gas environments, and indoors in food, medical and clean room manufacturing facilities. All models include features such as day/night functionality, video motion detection, Active Gatekeeper, support for AXIS Camera Application Platform, PoE, pixel counter, autotracking, WDR and edge storage.

## **AXIS Q6045/-E**

Indoor/outdoor high-speed PTZ dome with HDTV 1080p and 20x zoom

- Megapixel/HDTV: 2 MP/HDTV 1080p
- Max video resolution: 1920 x 1080
- 20x optical zoom
- Two-way audio\*)
- IP52-rated protection against dust and dripping water\*)
- Arctic Temperature Control\*\*)
- Vandal-resistant and shock detection

\*) AXIS Q6045

\*\*) AXIS Q6045-E



#### **AXIS Q6045-C**

High-speed HDTV 1080p PTZ dome with active cooling

- Megapixel/HDTV: 2 MP/HDTV 1080p
- Max video resolution: 1920 x 1080
- 20x optical zoom
- Operates in temperatures up to 75 °C (167 °F)
- Outdoor-ready, meeting military standard
- SFP slots for fiber, RJ45 connections
- Input/outport ports for external devices



## **AXIS Q6045-S**

Pressurized, stainless steel PTZ dome with HDTV 1080p and 20x zoom

- Megapixel/HDTV: 2 MP/HDTV 1080p
- Max video resolution: 1920 x 1080
- 20x optical zoom
- Marine-grade stainless steel
- Casing for pressurized nitrogen
- SFP slots for fiber, RJ45 connections >
- Input/outport ports for external devices



## **AXIS Q6044/-E**

Indoor/outdoor high-speed PTZ dome with HDTV 720p and 30x zoom

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720 >
- 30x optical zoom
- Two-way audio\*)
- IP52-rated protection against dust and dripping water\*)
- Arctic Temperature Control\*\*)
- Vandal-resistant and shock detection >
- Electronic image stabilization
- Automatic defog
- \*) AXIS Q6044 \*\*) AXIS Q6044-E



#### **AXIS Q.6044-C**

High-speed HDTV 720p PTC dome with active cooling

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720
- 30x optical zoom
- Operates in temperatures up to 75 °C (167 °F)
- Outdoor-ready, meeting military standard
- SFP slots for fiber, RJ45 connections
- Input/outport ports for external devices



#### **AXIS Q6044-S**

Pressurized, stainless steel PTZ dome with HDTV 720p and 30x zoom

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720
- 30x optical zoom
- Marine-grade stainless steel
- Casing for pressurized nitrogen
- SFP slots for fiber, RJ45 connections >
- Input/outport ports for external devices



## **AXIS Q6042/-E**

Indoor/outdoor high-speed PTZ dome with 36x zoom

- Max video resolution: Extended D1, 736 x 576 (50 Hz), 752 x 480 (60 Hz)
- 36x optical zoom
- Two-way audio\*) >
- IP52-rated protection against dust and dripping water\*)
- Arctic Temperature Control\*\*)
- Vandal-resistant and shock detection
- Electronic image stabilization



\*\*) AXIS Q6042-E



#### **AXIS Q6042-C**

High-speed PTZ dome with active cooling

- Max video resolution: Extended D1, 736 x 576 (50 Hz), 752 x 480 (60 Hz)
- 36x optical zoom
- Operates in temperatures up to 75 °C (167 °F)
- Outdoor-ready, meeting military standard
- SFP slots for fiber, RJ45 connections
- Input/outport ports for external devices



#### **AXIS Q6042-S**

Pressurized, stainless steel PTZ dome with 36x zoom

- Max video resolution: Extended D1, 736 x 576 (50 Hz), 752 x 480 (60 Hz)
- 36x optical zoom
- Marine-grade stainless steel
- Casing for pressurized nitrogen
- SFP slots for fiber, RJ45 connections
- Input/outport ports for external devices



## **AXIS P55 PTZ Dome Network Camera Series**

Advanced indoor and outdoor-ready PTZ domes

AXIS P55 PTZ Dome Network Camera Series consists of cost-effective, advanced indoor and outdoor-ready PTZ domes. They provide full frame rate video in resolutions up to HDTV 720p and with optical zoom up to 29x. In addition, the unique AXIS P5544 PTZ Dome Network Camera with Panopsis technology provides a 360° field of view that covers more than 950 m<sup>2</sup> (10,000 sq. ft.) — more than the size of three tennis courts — enabling panoramic views not only for security purposes, but also for crowd, flow and queue management.

The cameras enable surveillance of a large area and great details when zooming in. With quick and reliable installation features, the cameras are ideal for stores, banks, warehouses, parking lots, airports and train stations, as well as city and perimeter surveillance. All models include features such as day/night functionality, video motion detection, Advanced Gatekeeper, support for AXIS Camera Application Platform, PoE, pixel counter and edge storage.

#### **AXIS P5544**

HDTV PTZ dome with 360° panoramic view and 18x zoom

HDTV: HDTV 720p

Max video resolution: 1280 x 720

WDR

18x optical zoom

360° panoramic view >

Panopsis lens: 180° >

Two-way audio



## AXIS P5534/-E

Indoor/outdoor-ready HDTV PTZ dome with 18x zoom

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720
- 18x optical zoom
- IP66- and NEMA 4X-rated protection against dust, rain and snow\*)
- \*) AXIS P5534-E



## **AXIS P5532/-E**

Cost-effective PTZ dome camera with 29x zoom for indoor/outdoor applications

- Max video resolution: D1 720 x 576 (50 Hz), 720 x 480 (60 Hz)
- WDR
- 29x optical zoom
- Image stabilizer
- IP66- and NEMA 4X-rated protection against dust, rain and snow\*)
- \*) AXIS P5532-E



# **AXIS P5522/-E**

Affordable day/night PTZ dome with 18x zoom for broad indoor/outdoor application

- Max video resolution: D1 720 x 576 (50 Hz), 720 x 480 (60 Hz)
- WDR
- 18x optical zoom
- IP66- and NEMA 4X-rated protection against dust, rain and snow\*)
- \*) AXIS P5522-E



# **AXIS P5512/-E**

Compact, affordable indoor/outdoor-ready PTZ dome with 12x zoom

- Max video resolution: 4CIF 704 x 576 (50 Hz), 704 x 480 (60 Hz)
- 12x optical zoom
- IP66- and NEMA 4X-rated protection against dust, rain and snow\*)
- \*) AXIS P5512-E



## **AXIS P54 PTZ Dome Network Camera Series**

PTZ domes that blend in

AXIS P54 PTZ Dome Network Camera Series comprises outdoor-ready, wall-mounted HDTV pan/tilt/zoom cameras that are aesthetically designed to blend in with a building. The attractively priced cameras are ideal for use in city and perimeter surveillance, parking houses and school yards. AXIS P54 cameras mount directly on a wall without the traditional mounting arm. The design, which incorporates a wall bracket, allows the cameras to be at one with the building. The built-in bracket also provides cost savings by eliminating the need for a separate mounting accessory, and makes installation easier and quicker. The cameras' integrated sunshield can be easily repainted to match the color of the building. All models include features such as durable, low maintenance mechanics, 18x optical zoom, day/night functionality, two-way audio, input/output ports for external devices, video motion detection, audio detection, Advanced Gatekeeper, support for AXIS Camera Application Platform, PoE+, pixel counter and edge storage. The outdoor models have IP66 and NEMA 4X rating.

## **AXIS P5415-E**

Intelligent direct drive HDTV 1080p PTZ dome

- Megapixel/HDTV: 2 MP/HDTV 1080p
- Max video resolution: 1920 x 1080
- Outdoor wall-mount design for easy installation
- Repaintable integrated sunshield >
- Durable, low-maintenance mechanics
- 18x optical zoom
- Two-way audio
- 1/0s



#### **AXIS P5414-E**

Intelligent direct drive HDTV 720p PTZ dome

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720
- Outdoor wall-mount design for easy installation
- Repaintable integrated sunshield
- Durable, low-maintenance mechanics
- 18x optical zoom
- Two-way audio
- 1/0s



## **AXIS M50 PTZ Dome Network Camera Series**

Mini PTZ domes that give the big picture

AXIS M50 PTZ Dome Network Camera Series are affordably priced pan/tilt/zoom cameras. They are perfect for remote and discreet monitoring of indoor areas such as stores, banks, hotels, office lobbies, restaurants and warehouses. The vandal-resistant models can be used in those areas subject to vandalism. All models include features such as 3x digital zoom, video motion detection, support for AXIS Camera Application Platform, PoE, pixel counter and edge storage.

## AXIS M5014/-V

Mini HDTV PTZ dome that gives the big picture

- HDTV: HDTV 720p
- Max video resolution: 1280 x 720
- Vandal-resistant model\*)
- Two-way audio and built-in microphone\*\*)
- Ultra-discreet design\*\*)
- PoE
- IP66 and IK10 ratings\*)
- \*) AXIS M5014-V \*\*) AXIS M5014





## **AXIS M5013/-V**

Mini PTZ dome that gives the big picture

- Max video resolution: SVGA 800 x 600
- Vandal-resistant model\*)
- Two-way audio and built-in microphone\*\*)
- Ultra-discreet design\*\*)
- PoF
- IP66 and IK10 ratings\*)
- \*) AXIS M5013-V \*\*) AXIS M5013





## **AXIS 214 PTZ Network Camera**

Day & night camera with pan/tilt/zoom and audio

AXIS 214 PTZ Network Camera is a high performance camera for professional surveillance and remote monitoring. It combines a high quality color camera with the flexibility of remote pan/tilt/zoom through operator control. The 18x optical motorized lens with auto focus makes it possible to zoom in on a small or distant object with exceptional clarity. The AXIS 214 PTZ is designed for use in midsized businesses, such as retail stores and supermarkets. AXIS 214 include featureas such as day/night functionality, two-way audio, video motion detection and audio detection.

#### **AXIS 214 PTZ**

Day & night camera with pan/tilt/zoom and audio

Max video resolution: 4CIF 704 x 576 (50 Hz), 704 x 480 (60 Hz)

